

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Finale - Wachsversiegelung

Further trade names

Article number:

507 - 0001,

507 - 0006,

507 - 0001M,

507 - 0018,

507 - 6018.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Smoothing of wax surfaces

1.3. Details of the supplier of the safety data sheet

Company name: YETI Dentalprodukte GmbH

Street: Industriestrasse 3

Place: D-78234 Engen

Telephone: +49 7733-9410-0

Telefax: +49 7733-9410-22

Responsible Department: sdb@yeti-dental.com

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone

+49 7733-9410-0 (Mo-Do 8:00 - 16:30, Fr 8:00 - 15:00)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

1-methoxy-2-propanol; monopropylene glycol methyl ether

2-methylpropan-1-ol; iso-butanol

Signal word: Danger

Pictograms:



Hazard statements

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 2 of 11

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional advice on labelling

The product is labeled in accordance with Regulation (EC) no. 1272/2008 (GHS).

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64-17-5	ethanol, ethyl alcohol			65 - 80 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			10 - 20 %
	203-539-1	603-064-00-3	01-2119457435-35	
	Flam. Liq. 3, STOT SE 3; H226 H336			
78-83-1	2-methylpropan-1-ol; iso-butanol			2 - 10 %
	201-148-0	603-108-00-1	01-2119484609-23	
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 3 of 11

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of symptoms refer for medical treatment.

After inhalation

Ensure of fresh air. Get medical attention, if respiratory irritation develops or if breathing becomes difficult. In case of the person being unconscious put him/her in a stable side position.

After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Remove contact lens. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Rinse mouth. Do not induce vomiting. Do not give neutralising liquids. Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Vapours may cause drowsiness and dizziness. Following inhalation/eye contact: irritation of the mucous membranes, a numbing effect, impaired reaction times and sense of coordination are possible at high concentrations. Headache, dizziness, nausea, etc. may arise following prolonged inhalation of high vapour concentrations.

4.3. Indication of any immediate medical attention and special treatment needed

In case of the person being unconscious summon a doctor immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide and carbon dioxide. Vapours are heavier than air and spread along ground. Flashback at a long distance is possible.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Risk of bursting of the receptacle. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition. Single out leaking and leaky spray cans, empty and dispose them according to regulations. Avoid contact with skin, eyes and clothing. Do not breathe vapours. Do not breathe spray.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

For limiting emissions from volatile, organic compounds (VOC) solvent vapours are to be fed into a waste gas purification facility.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 4 of 11

6.3. Methods and material for containment and cleaning up

Pump off larger quantity.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal. Take measures against electrostatic charging. Use only non-sparking tools.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not keep containers unlocked. Handle in accordance with the general hygienic rules. When using do not eat, drink or smoke. Wash hands before breaks and at the end of workday. Take off contaminated clothing and wash it before reuse.

Observe the minimum standards in accordance with TRGS 500.

Advice on protection against fire and explosion

Do not smoke - volatile. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Use only explosion-proof equipment. Vapours are heavier than air and spread along ground. Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Store only in original container at temperature of 40°C maximum (=104°F).

7.3. Specific end use(s)

Adhesive for use in the field of dental technology

Holders / adhesive for wax parts

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 5 of 11

Protective and hygiene measures

Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. Chemical safety gloves made of butyl or nitrile rubber of category III according to EN 374. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Various, depending on coloration
Odour:	Solvent-like

		Test method
pH-Value:	Not applicable	DIN 19268

Changes in the physical state

Melting point:	Not determined	
Initial boiling point and boiling range:	68 °C	
Sublimation point:	Not determined	
Softening point:	Not determined	
Pour point:	Not determined	
Flash point:	12 °C	DIN 51755
Sustaining combustion:	No data available	

Flammability

Not determined

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated. Heating will cause pressure rise with risk of bursting.

Lower explosion limits:	1,5 vol. %
Upper explosion limits:	13 vol. %

Auto-ignition temperature

Not determined

Decomposition temperature:	Not applicable
----------------------------	----------------

Oxidizing properties

Not determined

Vapour pressure: (at 50 °C)	< 300 hPa
--------------------------------	-----------

Density (at 20 °C):	0,8 - 0,86 g/cm ³	ISO 2811-1
---------------------	------------------------------	------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 6 of 11

Water solubility: (at 20 °C)	Miscible
Partition coefficient:	Not determined
Viscosity / dynamic:	Not determined
Viscosity / kinematic:	Not determined
Flow time: (at 20 °C)	Not determined
Vapour density:	Not determined

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed. Protect from heat/ overheating. Risk of explosion.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Evolution of highly flammable gases/vapours.

10.4. Conditions to avoid

Vapours may form explosive mixture with air. (9°C)
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

Oxidizing agents (strong).

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 6200 mg/kg	Rat		
	inhalative (4 h) vapour	LC50 95,6 mg/l	Rat		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 11000 mg/kg	Rabbit		
	inhalative vapour	LC50 54,6 mg/l	Rat		
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Ratte		
	dermal	LD50 > 2000 mg/kg	Ratte		
	inhalative (4 h) vapour	LC50 > 24 mg/l	Ratte		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (1-methoxy-2-propanol; monopropylene glycol methyl ether)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50 8140 mg/l	96 h	Golden orfe		
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h	Daphnia magna		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna		
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 1430 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 1250 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 1439 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

All organic substances contained in the product correspond with the criteria of the test OECD 302 B and the values required for complete biodegradability in Regulation (EC) 648/2004 on Detergents.

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	- 0,31
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

This material and its container must be disposed of as hazardous waste. Where possible recycling is preferred to disposal.

The waste code number must be agreed with the disposer / manufacturer / competent authority.

Waste disposal number of waste from residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 9 of 11

080411 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); adhesive and sealant sludges containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste


Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Contaminated packagings are to be treated like the product itself.

SECTION 14: Transport information

Land transport (ADR/RID)


14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methylpropan-1-ol; iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methylpropan-1-ol; iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 10 of 11

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methylpropan-1-ol; iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methylpropan-1-ol; iso-butanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): > 90 %
Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Finale - Wachsversiegelung

Revision date: 01.02.2018

Product code: 11294-0007

Page 11 of 11

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

Update 2018

Abbreviations and acronyms

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (Agreement concerning the international carriage of Dangerous goods by Road)

IMDG-Code: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organisation (IATA: The International Air Transport Association)

GHS: Globally Harmonized System of Classification, Labelling and Packaging of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS-Nr.: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)