

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: GC Pattern Resin LS Liquid**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Auxillary for dental technology
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00
Fax +32/(0)16/40.26.84
msds@gc.dental
- **Further information obtainable from:** Regulatory affairs
- **1.4 Emergency telephone number:**
National poison center for United Kingdom of Great Britain and Northern Ireland:
Belfast: +44 28 90 63 2032
Birmingham: +44 121 507 4123
Edinburgh: +44 131 242 1383
Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180
Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 1)

- **Hazard-determining components of labelling:**

Methyl methacrylate
ethyl methacrylate
2-(2H-benzotriazol-2-yl)-p-cresol
Ethyleneglycol dimethacrylate

- **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:**

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-<75%
CAS: 6976-93-8 EINECS: 230-241-9	2-Methoxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-<25%
CAS: 97-63-2 EINECS: 202-597-5 Index number: 607-071-00-2	ethyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-<10%
CAS: 99-97-8 EINECS: 202-805-4 Index number: 612-056-00-9	N,N-dimethyl-p-toluidine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	1-<2.5%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 2)

CAS: 2440-22-4 EINECS: 219-470-5	2-(2H-benzotriazol-2-yl)-p-cresol Acute Tox. 2, H330; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.5-<1%
CAS: 97-90-5 EINECS: 202-617-2 Index number: 607-114-00-5	Ethyleneglycol dimethacrylate Skin Sens. 1, H317; STOT SE 3, H335	0.5-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Do not use mouth to mouth or mouth to nose resuscitation.

Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed Allergic reactions**

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 3)

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

- Remove persons from danger area.
- Keep away from ignition sources.
- Wear protective equipment. Keep unprotected persons away.
- Avoid contact with the eyes and skin.
- Wear protective clothing.

· **6.2 Environmental precautions:**

- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to penetrate the ground/soil.
- In case of seepage into the ground inform responsible authorities.
- Prevent seepage into sewage system, workpits and cellars.

· **6.3 Methods and material for containment and cleaning up:**

- Ensure adequate ventilation.
- Absorb liquid components with liquid-binding material.
- Dispose of the material collected according to regulations.

· **6.4 Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Avoid contact with the eyes and skin.

· **Information about fire - and explosion protection:**

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Do not spray onto a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

- Store in a cool location.
- Store only in unopened original receptacles.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Store in a cool place.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 4)

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:****80-62-6 Methyl methacrylate**

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm

· **DNELs****80-62-6 Methyl methacrylate**

Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)
Inhalative	DNEL inhalation	208 mg/m ³ (air) (worker, l. te., syst.)

· **PNECs****99-97-8 N,N-dimethyl-p-toluidine**

PNEC Aqua	152.59 µg/L (freshwater)
-----------	--------------------------

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Personal protective equipment:**· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Suitable respiratory protective device recommended.

· **Protection of hands:**

Protective gloves

· **Material of gloves**

e.g. KCL Butoject 897

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.29 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 2).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C

· Flash point: 10 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: Undetermined.

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:	2.1 Vol %
Upper:	12.5 Vol %

· Vapour pressure: Not determined.

· Density at 20 °C: 0.95 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	0.0 %
VOC (EC)	0.0 g/l

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 6)

- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
ATEmix (Oral) = 5284 mg/kg
ATEmix (dermal) > 4740 mg/kg
ATEmix (inhal.) = 15 mg/l

80-62-6 Methyl methacrylate

Oral	LD50	6000 mg/kg (rabbit)
Dermal	LD50	>5000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))

97-63-2 ethyl methacrylate

Oral	LD50	13424 mg/kg (rat (f+m))
Inhalative	LC50/4 h	55 mg/l (rat (f+m))

99-97-8 N,N-dimethyl-p-toluidine

Oral	LD50	1650 mg/kg (rat (f+m))
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	1.4 mg/l (rat (f+m))

2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol

Oral	LD50	10000 mg/kg (rat (f+m))
Inhalative	LC50/4 h	0.59 mg/l (rat (f+m))

97-90-5 Ethyleneglycol dimethacrylate

Oral	LD50	8700 mg/kg (rat (f+m))
Dermal	LD50	>2000 mg/kg (rat (f+m))

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Repeated dose toxicity** No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 7)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

99-97-8 N,N-dimethyl-p-toluidine	
LC50/96h	46 mg/L (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

18 00 00	WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care)
18 01 00	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 06*	chemicals consisting of or containing dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018



Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 8)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1247
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1247 METHYL METHACRYLATE MONOMER, STABILIZED METHYL METHACRYLATE MONOMER, STABILIZED
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 339 F-E,S-D B SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ)	1L

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 9)

· Exempted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, , II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Classification according to Regulation (EC) No 1272/2008** Calculation method
- **Department issuing SDS:** Regulatory affairs
- **Contact:** msds@gc.dental
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.08.2018

Version number 7

Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 10)

*Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***· Sources**

- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

· * Data compared to the previous version altered.*This version replaces all previous versions.***Disclaimer:**

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.